

(Note: Edit these specifications to fit your project detail. Samples and estimating examples are available through [www.SnoGuard.com](http://www.SnoGuard.com), e-mail [sales@SnoGuard.com](mailto:sales@SnoGuard.com) or call 708.485-6272.)

## **Section 07 72 53 Roof Accessories – Snow Guards**

### **(Gough SnoGuard Type SGVLS Specification Sheet for Vande Hey Lightweight Slate Roofing)**

#### **PART 1 – GENERAL REQUIREMENTS**

##### **1.01 SUMMARY**

###### **A. DESCRIPTION OF WORK**

1. Install Gough SnoGuard Type SGVLS snow guards for slate roofs.
2. Assure proper positioning of snow guards with roof installation.
3. Use proper fasteners for mechanical attachment.

###### **B. RELATED SECTIONS**

1. Section 07600 / Flashing and Sheet Metal / MasterFormat™ 2004 07 60 00
2. Section 07310 / Roofing Shingles / MasterFormat™ 2004 07 31 00
3. Section 07710 / Prefabricated Roof Specialties / 2004
4. Division 7: Thermal and Moisture Protection.

##### **1.02 SUBMITTALS**

- A. PRODUCT DATA: Submit manufacturer's product data & installation instructions.
- B. SHOP DRAWINGS: If not clearly shown on project drawings, submit roof drawing showing locations of all Gough SnoGuard Type SGVLS snow guards and attachment spacing.
- C. SAMPLES: Submit sample of one Type SGVLS snow guard as requested.

##### **1.03 QUALITY ASSURANCE:**

- A. INSTALLER: Installer is to be experienced in the installation of specified roofing material and snow guards for not less than 5 years in the area of the project.
- B. FASTENERS: Should be selected for compatibility with snow guard and roof deck.
- C. CODE COMPLIANCE: Comply with all applicable local, state, and national building codes, as well as OSHA regulations.
- D. STORAGE: Boxes containing Gough SnoGuards should be stored in a dry place until ready for use.

#### **PART 2 – PRODUCTS**

##### **2.1 MANUFACTURER**

- A. Gough SnoGuards, 4133 Du Bois Blvd., Brookfield, IL 60513-1809, voice (708) 485-6272, fax (708) 485-6273, e-mail: [Sales@SnoGuard.com](mailto:Sales@SnoGuard.com), Web Site: [www.SnoGuard.com](http://www.SnoGuard.com)

##### **2.2 MATERIAL**

- A. 24 oz. cold rolled copper
- B. With double pedestal

##### **2.3 FINISH**

- A. Copper

#### **PART 3 - EXECUTION**

##### **3.01 EXAMINATION**

- A. Substrate: Inspect roof system to be properly attached and installed to withstand additional loading incurred. Notify General Contractor of any deficiencies before installing Gough SnoGuards.

##### **3.02 INSTALLATION**

- A. Comply with architectural drawings for placement & Manufacturer's instructions for installation. Contact Manufacturer for sample layouts if needed.<sup>1</sup>